

SYSTEM AND METHOD FOR MAKING TELECOMMUNICATION CALLS

BACKGROUND OF THE INVENTION

5

Field Of The Invention

The present invention relates to the field of telecommunications, and more
10 particularly, an improved calling procedure.

Background Information

15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000
1005
1010
1015
1020
1025
1030
1035
1040
1045
1050
1055
1060
1065
1070
1075
1080
1085
1090
1095
1100
1105
1110
1115
1120
1125
1130
1135
1140
1145
1150
1155
1160
1165
1170
1175
1180
1185
1190
1195
1200
1205
1210
1215
1220
1225
1230
1235
1240
1245
1250
1255
1260
1265
1270
1275
1280
1285
1290
1295
1300
1305
1310
1315
1320
1325
1330
1335
1340
1345
1350
1355
1360
1365
1370
1375
1380
1385
1390
1395
1400
1405
1410
1415
1420
1425
1430
1435
1440
1445
1450
1455
1460
1465
1470
1475
1480
1485
1490
1495
1500
1505
1510
1515
1520
1525
1530
1535
1540
1545
1550
1555
1560
1565
1570
1575
1580
1585
1590
1595
1600
1605
1610
1615
1620
1625
1630
1635
1640
1645
1650
1655
1660
1665
1670
1675
1680
1685
1690
1695
1700
1705
1710
1715
1720
1725
1730
1735
1740
1745
1750
1755
1760
1765
1770
1775
1780
1785
1790
1795
1800
1805
1810
1815
1820
1825
1830
1835
1840
1845
1850
1855
1860
1865
1870
1875
1880
1885
1890
1895
1900
1905
1910
1915
1920
1925
1930
1935
1940
1945
1950
1955
1960
1965
1970
1975
1980
1985
1990
1995
2000
2005
2010
2015
2020
2025
2030
2035
2040
2045
2050
2055
2060
2065
2070
2075
2080
2085
2090
2095
2100
2105
2110
2115
2120
2125
2130
2135
2140
2145
2150
2155
2160
2165
2170
2175
2180
2185
2190
2195
2200
2205
2210
2215
2220
2225
2230
2235
2240
2245
2250
2255
2260
2265
2270
2275
2280
2285
2290
2295
2300
2305
2310
2315
2320
2325
2330
2335
2340
2345
2350
2355
2360
2365
2370
2375
2380
2385
2390
2395
2400
2405
2410
2415
2420
2425
2430
2435
2440
2445
2450
2455
2460
2465
2470
2475
2480
2485
2490
2495
2500
2505
2510
2515
2520
2525
2530
2535
2540
2545
2550
2555
2560
2565
2570
2575
2580
2585
2590
2595
2600
2605
2610
2615
2620
2625
2630
2635
2640
2645
2650
2655
2660
2665
2670
2675
2680
2685
2690
2695
2700
2705
2710
2715
2720
2725
2730
2735
2740
2745
2750
2755
2760
2765
2770
2775
2780
2785
2790
2795
2800
2805
2810
2815
2820
2825
2830
2835
2840
2845
2850
2855
2860
2865
2870
2875
2880
2885
2890
2895
2900
2905
2910
2915
2920
2925
2930
2935
2940
2945
2950
2955
2960
2965
2970
2975
2980
2985
2990
2995
3000
3005
3010
3015
3020
3025
3030
3035
3040
3045
3050
3055
3060
3065
3070
3075
3080
3085
3090
3095
3100
3105
3110
3115
3120
3125
3130
3135
3140
3145
3150
3155
3160
3165
3170
3175
3180
3185
3190
3195
3200
3205
3210
3215
3220
3225
3230
3235
3240
3245
3250
3255
3260
3265
3270
3275
3280
3285
3290
3295
3300
3305
3310
3315
3320
3325
3330
3335
3340
3345
3350
3355
3360
3365
3370
3375
3380
3385
3390
3395
3400
3405
3410
3415
3420
3425
3430
3435
3440
3445
3450
3455
3460
3465
3470
3475
3480
3485
3490
3495
3500
3505
3510
3515
3520
3525
3530
3535
3540
3545
3550
3555
3560
3565
3570
3575
3580
3585
3590
3595
3600
3605
3610
3615
3620
3625
3630
3635
3640
3645
3650
3655
3660
3665
3670
3675
3680
3685
3690
3695
3700
3705
3710
3715
3720
3725
3730
3735
3740
3745
3750
3755
3760
3765
3770
3775
3780
3785
3790
3795
3800
3805
3810
3815
3820
3825
3830
3835
3840
3845
3850
3855
3860
3865
3870
3875
3880
3885
3890
3895
3900
3905
3910
3915
3920
3925
3930
3935
3940
3945
3950
3955
3960
3965
3970
3975
3980
3985
3990
3995
4000
4005
4010
4015
4020
4025
4030
4035
4040
4045
4050
4055
4060
4065
4070
4075
4080
4085
4090
4095
4100
4105
4110
4115
4120
4125
4130
4135
4140
4145
4150
4155
4160
4165
4170
4175
4180
4185
4190
4195
4200
4205
4210
4215
4220
4225
4230
4235
4240
4245
4250
4255
4260
4265
4270
4275
4280
4285
4290
4295
4300
4305
4310
4315
4320
4325
4330
4335
4340
4345
4350
4355
4360
4365
4370
4375
4380
4385
4390
4395
4400
4405
4410
4415
4420
4425
4430
4435
4440
4445
4450
4455
4460
4465
4470
4475
4480
4485
4490
4495
4500
4505
4510
4515
4520
4525
4530
4535
4540
4545
4550
4555
4560
4565
4570
4575
4580
4585
4590
4595
4600
4605
4610
4615
4620
4625
4630
4635
4640
4645
4650
4655
4660
4665
4670
4675
4680
4685
4690
4695
4700
4705
4710
4715
4720
4725
4730
4735
4740
4745
4750
4755
4760
4765
4770
4775
4780
4785
4790
4795
4800
4805
4810
4815
4820
4825
4830
4835
4840
4845
4850
4855
4860
4865
4870
4875
4880
4885
4890
4895
4900
4905
4910
4915
4920
4925
4930
4935
4940
4945
4950
4955
4960
4965
4970
4975
4980
4985
4990
4995
5000
5005
5010
5015
5020
5025
5030
5035
5040
5045
5050
5055
5060
5065
5070
5075
5080
5085
5090
5095
5100
5105
5110
5115
5120
5125
5130
5135
5140
5145
5150
5155
5160
5165
5170
5175
5180
5185
5190
5195
5200
5205
5210
5215
5220
5225
5230
5235
5240
5245
5250
5255
5260
5265
5270
5275
5280
5285
5290
5295
5300
5305
5310
5315
5320
5325
5330
5335
5340
5345
5350
5355
5360
5365
5370
5375
5380
5385
5390
5395
5400
5405
5410
5415
5420
5425
5430
5435
5440
5445
5450
5455
5460
5465
5470
5475
5480
5485
5490
5495
5500
5505
5510
5515
5520
5525
5530
5535
5540
5545
5550
5555
5560
5565
5570
5575
5580
5585
5590
5595
5600
5605
5610
5615
5620
5625
5630
5635
5640
5645
5650
5655
5660
5665
5670
5675
5680
5685
5690
5695
5700
5705
5710
5715
5720
5725
5730
5735
5740
5745
5750
5755
5760
5765
5770
5775
5780
5785
5790
5795
5800
5805
5810
5815
5820
5825
5830
5835
5840
5845
5850
5855
5860
5865
5870
5875
5880
5885
5890
5895
5900
5905
5910
5915
5920
5925
5930
5935
5940
5945
5950
5955
5960
5965
5970
5975
5980
5985
5990
5995
6000
6005
6010
6015
6020
6025
6030
6035
6040
6045
6050
6055
6060
6065
6070
6075
6080
6085
6090
6095
6100
6105
6110
6115
6120
6125
6130
6135
6140
6145
6150
6155
6160
6165
6170
6175
6180
6185
6190
6195
6200
6205
6210
6215
6220
6225
6230
6235
6240
6245
6250
6255
6260
6265
6270
6275
6280
6285
6290
6295
6300
6305
6310
6315
6320
6325
6330
6335
6340
6345
6350
6355
6360
6365
6370
6375
6380
6385
6390
6395
6400
6405
6410
6415
6420
6425
6430
6435
6440
6445
6450
6455
6460
6465
6470
6475
6480
6485
6490
6495
6500
6505
6510
6515
6520
6525
6530
6535
6540
6545
6550
6555
6560
6565
6570
6575
6580
6585
6590
6595
6600
6605
6610
6615
6620
6625
6630
6635
6640
6645
6650
6655
6660
6665
6670
6675
6680
6685
6690
6695
6700
6705
6710
6715
6720
6725
6730
6735
6740
6745
6750
6755
6760
6765
6770
6775
6780
6785
6790
6795
6800
6805
6810
6815
6820
6825
6830
6835
6840
6845
6850
6855
6860
6865
6870
6875
6880
6885
6890
6895
6900
6905
6910
6915
6920
6925
6930
6935
6940
6945
6950
6955
6960
6965
6970
6975
6980
6985
6990
6995
7000
7005
7010
7015
7020
7025
7030
7035
7040
7045
7050
7055
7060
7065
7070
7075
7080
7085
7090
7095
7100
7105
7110
7115
7120
7125
7130
7135
7140
7145
7150
7155
7160
7165
7170
7175
7180
7185
7190
7195
7200
7205
7210
7215
7220
7225
7230
7235
7240
7245
7250
7255
7260
7265
7270
7275
7280
7285
7290
7295
7300
7305
7310
7315
7320
7325
7330
7335
7340
7345
7350
7355
7360
7365
7370
7375
7380
7385
7390
7395
7400
7405
7410
7415
7420
7425
7430
7435
7440
7445
7450
7455
7460
7465
7470
7475
7480
7485
7490
7495
7500
7505
7510
7515
7520
7525
7530
7535
7540
7545
7550
7555
7560
7565
7570
7575
7580
7585
7590
7595
7600
7605
7610
7615
7620
7625
7630
7635
7640
7645
7650
7655
7660
7665
7670
7675
7680
7685
7690
7695
7700
7705
7710
7715
7720
7725
7730
7735
7740
7745
7750
7755
7760
7765
7770
7775
7780
7785
7790
7795
7800
7805
7810
7815
7820
7825
7830
7835
7840
7845
7850
7855
7860
7865
7870
7875
7880
7885
7890
7895
7900
7905
7910
7915
7920
7925
7930
7935
7940
7945
7950
7955
7960
7965
7970
7975
7980
7985
7990
7995
8000
8005
8010
8015
8020
8025
8030
8035
8040
8045
8050
8055
8060
8065
8070
8075
8080
8085
8090
8095
8100
8105
8110
8115
8120
8125
8130
8135
8140
8145
8150
8155
8160
8165
8170
8175
8180
8185
8190
8195
8200
8205
8210
8215
8220
8225
8230
8235
8240
8245
8250
8255
8260
8265
8270
8275
8280
8285
8290
8295
8300
8305
8310
8315
8320
8325
8330
8335
8340
8345
8350
8355
8360
8365
8370
8375
8380
8385
8390
8395
8400
8405
8410
8415
8420
8425
8430
8435
8440
8445
8450
8455
8460
8465
8470
8475
8480
8485
8490
8495
8500
8505
8510
8515
8520
8525
8530
8535
8540
8545
8550
8555
8560
8565
8570
8575
8580
8585
8590
8595
8600
8605
8610
8615
8620
8625
8630
8635
8640
8645
8650
8655
8660
8665
8670
8675
8680
8685
8690
8695
8700
8705
8710
8715
8720
8725
8730
8735
8740
8745
8750
8755
8760
8765
8770
8775
8780
8785
8790
8795
8800
8805
8810
8815
8820
8825
8830
8835
8840
8845
8850
8855
8860
8865
8870
8875
8880
8885
8890
8895
8900
8905
8910
8915
8920
8925
8930
8935
8940
8945
8950
8955
8960
8965
8970
8975
8980
8985
8990
8995
9000
9005
9010
9015
9020
9025
9030
9035
9040
9045
9050
9055
9060
9065
9070
9075
9080
9085
9090
9095
9100
9105
9110
9115
9120
9125
9130
9135
9140
9145
9150
9155
9160
9165
9170
9175
9180
9185
9190
9195
9200
9205
9210
9215
9220
9225
9230
9235
9240
9245
9250
9255
9260
9265
9270
9275
9280
9285
9290
9295
9300
9305
9310
9315
9320
9325
9330
9335
9340
9345
9350
9355
9360
9365
9370
9375
9380
9385
9390
9395
9400
9405
9410
9415
9420
9425
9430
9435
9440
9445
9450
9455
9460
9465
9470
9475
9480
9485
9490
9495
9500
9505
9510
9515
9520
9525
9530
9535
9540
9545
9550
9555
9560
9565
9570
9575
9580
9585
9590
9595
9600
9605
9610
9615
9620
9625
9630
9635
9640
9645
9650
9655
9660
9665
9670
9675
9680
9685
9690
9695
9700
9705
9710
9715
9720
9725
9730
9735
9740
9745
9750
9755
9760
9765
9770
9775
9780
9785
9790
9795
9800
9805
9810
9815
9820
9825
9830
9835
9840
9845
9850
9855
9860
9865
9870
9875
9880
9885
9890
9895
9900
9905
9910
9915
9920
9925
9930
9935
9940
9945
9950
9955
9960
9965
9970
9975
9980
9985
9990
9995
10000
10005
10010
10015
10020
10025
10030
10035
10040
10045
10050
10055
10060
10065
10070
10075
10080
10085
10090
10095
10100
10105
10110
10115
10120
10125
10130
10135
10140
10145
10150
10155
10160
10165
10170
10175
10180
10185
10190
10195
10200
10205
10210
10215
10220
10225
10230
1023

For example, "2", "A", "B", and "C" all share the key corresponding to the numeral "2." Thus, the system cannot distinguish between these four characters. A telephone effectively recognizes "2", "A", "B", and "C" as all being the same character. Thus, a caller can only choose seven characters, each of which can be one of 10 actual/unique "buttons." This affects real world choices of mnemonics. For example, suppose someone wanted the phone number "hotdogs." The user would be prevented from taking this if someone had already taken "hotfogs." Even though these mnemonics are alphabetically different, they map to the same keypad numbers: 468-3647. What is more, "hotdogs" would not be available if the telephone number 468-3647 is already assigned to a caller.

Another disadvantage of using mnemonic telephone numbers is that not all seven digit combinations in an area code could ever correspond to meaningful mnemonics. For example, some seven digit combinations, when considered in terms of the characters available for each letter, could never make phonetic or literal sense in English or other western languages. One example of this is 999-9997 in which, according to the keypad's labeling, 9 can be W, X, or Y and 7 can be P, R, or S. Hence, of all the phone numbers available, there are only a few of them could be potential mnemonics. It is further clear, therefore, that despite the obvious benefits of mnemonic telephone numbers, such a system results in many unused telephone numbers. The current system also requires telephone users to know the area code that the number is in and dial it before the mnemonic.

A person who has trouble remembering a telephone number or area code of a mnemonic may attempt to use directory assistance. However, this system also has drawbacks. Firstly, using directory assistance can be expensive. Secondly, it is time consuming as a user must answer a series of questions in order to get the number. Conventional directory assistance requires one to know not only the full name of the party that they wish to call, but often the city and street as well. Certain enhanced directory services advertise allowing a user to find a listing without knowing, for example, the name of the city or the full name of the business. However,

enhanced directory services are often more expensive than conventional ones, and they are also time consuming in that they require the user to answer a series of questions as the operator or computer needs to collect information to use in searching the directory database. Thus, it is more expensive and time consuming to use than to direct dial using a number or mnemonic.

5

SUMMARY OF THE INVENTION

The system and method are directed to an improved calling procedure. In a preferred embodiment, instead of dialing telephone numbers, callers enter mnemonic, alphanumeric "phone addresses" (PA's). PA's may be entered using methods such as telephone keypad entry, keyboard entry, voice input, and handwriting input. A reference table, such as a database, lookup table, or the like, associates these phone addresses with actual telephone numbers. Accordingly, when caller enters a PA, the system connects the caller to the corresponding telephone number. In one embodiment, restrictions may be put into place whereby a caller must fulfill certain requirements, such as physical location or personal identity, to be connected to the corresponding telephone number. Additionally, in another embodiment, two or more parties may share the same PA. If a caller enters such a PA, the system acts in order to determine which of the parties who share that PA the caller wishes and/or is entitled to reach.

10

15

20

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 illustrates a conventional phone system with the addition of a phone address apparatus of the present invention.

25

Fig. 2 illustrates examples of decoders and converters of certain embodiments of the present invention.

Fig. 3 illustrates the functionality of the decoder unit of the phone address apparatus.

Fig. 4 illustrates the functionality of the decoding process of Fig. 3 in more detail when keypad or numeric keypad entry is used.

Fig. 5 illustrates the functionality of the converter unit of the phone address apparatus.

Fig. 6 illustrates the functionality of the ambiguity resolving process of Fig. 5 in more detail.

Fig. 7 illustrates an example of a reference table that is used in one embodiment of the present invention.

10

DETAILED DESCRIPTION OF THE INVENTION

The system and method are directed to an improved calling procedure. In a preferred embodiment, instead of dialing telephone numbers, callers enter mnemonic, alphanumeric "phone addresses" (PA's). A reference table, such as a database, lookup table, or the like, associates these phone addresses with actual telephone numbers, along with their area codes and country codes as necessary. If the caller enters a PA that is numerically identical to a standard telephone number, the system will connect the caller to the party that corresponds to this telephone number.

In another embodiment, two or more parties may register the same PA. The system then considers such a PA to be "ambiguous." If a caller enters an ambiguous PA, the system then resolves the ambiguity in order to determine which of the parties who share that PA the caller wishes to reach. For example, the system may make this determination by asking the caller questions, based on the identity of the caller (perhaps determined by voice sample), based on the present physical location of the caller, based on the telephone phone number from which the user is calling, and/or other parameters. In some cases, the resolution of ambiguity step might determine that the caller, for example because of his location and/or identity, is not entitled to be

connected to any of the parties who have registered a particular PA. Thus, for a particular caller, a PA registered by two or more parties may map to no telephone numbers.

A PA need not necessarily map to more than one telephone number to be considered "ambiguous" by the system. A PA which maps to only one phone number may be considered to be ambiguous when it maps to its one phone number with restriction. A PA maps with restriction when the PA only connects a caller to a particular phone number when one or more conditions are met. An example is a PA that maps to one phone number, but with a restriction based on the identity of the caller wherein only certain callers entering the PA are connected to the corresponding phone number. In this example the system resolves the ambiguity by determining the identity of the caller. The system then determines if the caller should be connected to the corresponding telephone number.

The PA's are strings of numbers and letters of a length determined by the provider. In one embodiment, the maximum length of a PA is greater than seven characters. For example, the maximum length may be 32 characters.

The Calling System

In Fig. 1, a conventional telephone 100 is connected to its local central office (CO) 101. The central office is connected to the public switched telephone network (PSTN) 106. Although one conventional telephone and one central office are shown for ease of description, there may be a plurality of CO's 101 connected to the PSTN, and a plurality of telephones connected to each CO 101. Further, although the network described is the PSTN, any network capable of handling calls using dialed characters may be used. Likewise, in addition to telephones, any device capable of completing calls using characters may be used.

Further shown in Fig. 1, a plurality of base stations 108 are connected to a central controller (CC) 107, which is in turn connected the local central office 101 via interconnection

line 151. A plurality of mobile units 109 communicate with the base stations 108. Although one central controller is shown for ease of description, there may be a plurality of CC's 107 in the network, each connected to one of the plurality of CO's 101.

The CO 101 contains a digital switching apparatus, with a channel bank
5 interfacing the analog telephone 100 with the digital switch. This central office further includes at least one PA apparatus 103. The PA apparatus 103 provides the functionality described wherein in which a caller may pick up his phone, enter a PA, and ultimately be connected to the appropriate party. The user may enter the phone address by speaking the phone address into the mouthpiece, typing it on an alphanumeric keyboard operationally attached to telephone 100, by
10 typing it on the telephone's standard keypad/numeric keypad using the keypads alphanumeric labeling, or by similar methods. Other entry methods can be used as well, such as handwriting recognition. In one embodiment, a user does not enter an access code or dial an access number before entering a PA. In another embodiment the system could be configured so that a user would first call a gateway using standard dialing methods, and once connected to this gateway would enter the PA. In order to select among various communications providers, the user might
15 enter a code before entering the PA. Alternately, the code might act as a lock-out password by which a person could not make calls without knowing the password.

The PA apparatus 103 is made up of two logical units, a decoder and a converter. In practice, these two units may be either physically separate or combined into one unit. For
20 example, Fig. 2a shows a decoder 210 and a converter 211 as two separate units. Fig. 2b shows a combined unit 212 which performs both decoding and conversion functions. In one embodiment, each of decoder 210, converter 211, and combined unit 212 contains read-only memory (ROM) 223 for holding data and program code which do not need to be changed frequently or on-the-fly, random access memory (RAM) 221 for holding data and program code
25 which need to be changed frequently or on-the-fly, and one or more processors (CPU's) 220 operatively connected to the RAM and ROM whereby the processors may execute the program

code and/or manipulate the code and/or data. CPU 220 may each be commonly known processor such as an IBM or Motorola PowerPC or an Intel Pentium. In one embodiment, decoding operations, converting operations, or both are performed by a general purpose computer 213 as shown in Fig. 2c which has been programmed to perform these operations as described herein.

5 The phrases “general purpose computer,” “computer,” and the like, as used herein, refer but are not limited to an engineering workstation, PC, Macintosh, PDA, web-enabled cellular phone and the like. The phrases “General purpose computer,” “computer,” and the like also refer, but are not limited to, one or more processors operatively connected to one or more memory or storage units, wherein the memory or storage may contain data, algorithms, and/or
10 program code, and the processor or processors may execute the program code and/or manipulate the program code, data, and/or algorithms. Accordingly, computer 213 as shown in this example includes system bus 2050 which operatively connects two processors 2051 and 2052, random access memory (RAM) 2053, read-only memory (ROM) 2055, input output (I/O) interfaces 2057 and 2058, storage interface 2059, and display interface 2061. Storage interface 2059 in turn
15 connects to mass storage 2063. Each of I/O interfaces 2057 and 2058 may be an Ethernet, IEEE 1394, IEEE 802.11, Signaling System 7 (SS7), or other interface such as is known in the art. Mass storage 2063 may be a hard drive, optical disk, or the like. Processors 2057 and 2058 may each be a commonly known processor such as an IBM or Motorola PowerPC or an Intel Pentium. Computer 213 may use an operating system known in the art such as Apple Computer’s
20 OS X, Microsoft’s Windows 95/98/NT/Me, or a Unix variant or derivative such as Sun Microsystems’s Solaris.

Computer 213 as shown in this example also includes an LCD display unit 2001, a keyboard 2002 and a mouse 2003. In alternate embodiments, keyboard 2002 and/or mouse 2003 might be replaced with a pen interface. Computer 213 may additionally include or be
25 attached to card readers, DVD drives, or floppy disk drives whereby media containing program code may be inserted for the purpose of loading the code onto the computer.

Conventional telephone 100 connects to its local CO 101, which in turn notes the telephone number dialed and takes steps which culminate in the connection of the caller to the party indicated by the telephone number. The CO 101 shown in Fig. 1 additionally contains a PA apparatus 103. In the preferred embodiment, the user may enter the PA by speaking the phone address into the mouthpiece, typing it on an alphanumeric keyboard operationally attached to telephone 100, typing it on the standard tone keypad using the keypads alphanumeric labeling, or by similar methods. As will be described in more detail herein, the PA apparatus 103 then intercepts the entered PA, decodes it into a format ready for conversion, converts the decoded PA into the corresponding telephone number (obtaining additional information if necessary to solve an ambiguity), and outputs the phone number to the portions of the CO 101 that accept a phone number. The CO 101 then connects the call placed on phone 100 to the party indicated by the resolved phone number.

Similarly, the CC 107 operates in a manner similar to that of a conventional cellular central controller, but with the addition of the PA apparatus 103's functionality. A user may enter a phone address by speaking the phone address into the mouthpiece of a mobile 109, typing it on an alphanumeric keyboard operationally attached to mobile 109, typing it on the mobile's numeric keypad using the keypads alphanumeric labeling, or by similar methods. As will be described in more detail herein, the PA apparatus 103 then intercepts the entered PA, decodes it into a format ready for conversion, converts the decoded PA into the corresponding telephone number (obtaining additional information if necessary to solve an ambiguity), and outputs the phone number to the portions of the central controller that expect a phone number. The CO 101 then connects the call placed on mobile unit 109 to the party indicated by the resolved phone number.

The converter of 211, 212 or 213, uses a reference table, preferably stored in its RAM or in an attached hard drive, in order to convert a PA to a phone number. One or more central locations 116 contain master reference tables 700. An "update line" 114 allows the

reference table 700 associated with the converter 211, 212 or 213 to be updated, according to a schedule, from one or more central locations 116, whereby the reference table associated with the converter will be a periodically updated copy of the master table. In one embodiment, additions and amendments may be made only to a master table, with the changes being propagated to the reference tables associated with the converters according to a schedule. The schedule may be set up such that updating occurs every so many units of time, whenever a change is made to the master table, or both. The updating may be achieved according to the conventional methods of replicated servers known in the art. Further, the master tables in the central locations 116 are preferably stored on replicated servers, wherein a change made to any is made to all, using the conventional methods of replicated servers known in the art. Update line 114 may provide connection to 116 via the internet, a dedicated T1 line, a satellite link, or by similar methods obvious to one well versed in the art.

Although the PA apparatus is shown here as being integrated into the central office or central controller, it will be obvious to one well-versed in the art that it may be placed at other logical locations within telephone system. For example, the PA apparatus 103 may be placed apart from, but functionally connected to, either the central office or the central controller. In some embodiments, this connection may include a Signaling System 7 (SS 7) interface as is known in the art. In another example, the PA apparatus might be placed on a customer's premises, so that it interfaces between the customer's telephones and his interface to the telephone network. In a further alternate embodiment, the PA apparatus may be integrated into the telephone or the mobile unit.

Operation of the Decoder Unit

Fig. 3 is a flow chart showing the specifics of the operation of the decoder unit 210, 212 or 213.

In step 301, the decoder 210, 212 or 213 accepts the PA entry from the user, and determines the entry modality. In one embodiment, three entry modalities are used: voice, keypad, and alphanumeric keyboard. Other entry methods may also be used.

In step 302, the decoder 210, 212 or 213 decodes the PA entry into a format that the converter unit 211, 212 or 213 can understand. The decoding method will depend on whether the decoder 210, 212 or 213 determined the entry method to be voice, keypad, alphanumeric pad, or another entry method.

In step 303, the decoder 210, 212 or 213 determines if the decoding of step 302 is successful (i.e., if it was able to decode the PA entry). If it is not successful, the system proceeds to step 304 in which the caller is notified of the error and is prompted to re-enter the PA. In an alternate embodiment, instead of giving the caller an opportunity to re-enter the PA, the call may terminate. If the decoding step was successful, the process proceeds to step 305 in which the decoded PA is outputted to converter 211, 212 or 213. In some cases, this outputting step may involve transferring the decoded PA via Ethernet, IEEE 1394, IEEE 802.11, a common bus, or some other means connecting the decoder and converter. In other cases, this step may involve transferring the decoded PA between functions or objects of a program or programs running on the converter and/or decoder.

In the case of voice input, step 302 will execute one of the many speech recognition algorithms known in the art. For example, if ASCII text is the format the converter 211, 212 or 213 can understand, in step 302 the PA spoken by the user will be converted into ASCII text. In the case of alphanumeric keypad entry, the converter 211, 212, or 213 converts the data received from the keyboard into the format that is expected by the converter using conventional methods for reading keyboard input. For example if ASCII text is the format the converter 211, 212 or 213 can understand, the PA typed by the user will be converted into ASCII text using conventional methods.

In the case of keypad or numeric keypad input, the converter 211, 212, or 213 converts the data received from the keyboard into ASCII text, or whatever input the converter receives. There are special considerations for the case of such pad input because of the ambiguity of the pad in which, for example, 5, J, K and L all share the same key such that when a user presses this key there is no way to know which of the four characters was meant by the user. The method for resolving this ambiguity in order to achieve step 302 for keypad PA input is described in Fig. 4.

Operation of the Decoder Unit: Resolution of Ambiguity

Fig. 4 discloses converter 211, 212 or 213's method for resolving the above-described keypad ambiguity when performing decoding step 302 for keypad PA input. In step 402 the decoder 210, 212 or 213 consults the reference table to see which preregistered PA's ambiguously correspond to the sequence of keypad presses. For example suppose the following keys were pressed:

[4 GHI] [2 ABC] [8 TUV] [3 DEF] [2 ABC] [6 MNO] [6 MNO] [7 PRS] [2 ABC] [6 MNO] [9 WXY]

Referring to sample reference table (Fig. 7), the preregistered PA's HAVECOMPANY and HATECOMPANY, due to the keypad's ambiguity, could have been meant by the keys that were pressed. Although this example shows two preregistered PA's being returned for the particular keypad sequence, in real-world operation the reference table could show that none, one, or several PA's correspond to a particular keypad sequence. In step 403 converter 211, 212 or 213 determines how many PA's were returned at step 402. If no preregistered PA's were found to correspond to the keys pressed, the process proceeds to step 404 in which the caller is told of the error, and then to step 301, whereby the caller is given the opportunity to reenter the PA. In an alternate embodiment, the converter 211, 212 or 213 may

terminate the call after telling the user of the error in step 404. If in step 403 the converter finds that step 402 resulted in only one match, the process proceeds to step 409. If the sequences of keypad presses is not unique, that is if the converter 211, 212 or 213 finds that step 402 resulted in a plurality of matches, the flow proceeds to step 406.

5 In step 406, the user is told to select the PA that he intended from the list of PA's that ambiguously correspond to the entered keypad sequence, or to choose "none of the above." This could be done by the converter 211, 212 or 213 sending a message to a display screen operatively attached to telephone 100, using voice synthesis to output the message through the speaker or earpiece of telephone 100, or by other methods that are well known in the art. In one
10 embodiment, the user will select his intended PA using the keypad. Thus, the converter 211, 212 or 213 might ask the user to "press 1 for 'hate company,' press 2 for 'have company', or press 3 for none of the above."

In another embodiment, voice input may be used, such a method using a voice recognition method that is well known in the art. The user could be asked to "say 1 for 'hate company', say 2 for 'have company' or say 3 for 'none of the above'." The converter 211, 212 or 213 could use conventional voice-recognition methods to obtain the user's response.

15 In step 407 converter 211, 212 or 213 determines whether the user selected "none of the above." In such a case, the system proceeds to step 404 in which the user is notified of the error and then to step 301, whereby the caller is given the opportunity to reenter the PA. In an
20 alternate embodiment, the system may terminate the call after telling the user of the error in step 404. If the user does not select "none of the above," the sequence will proceed to step 409 in which the reference table provides the PA corresponding the user's choice in step 406. The system then proceeds to step 303 of Fig. 3.

25 **Operation of the Converter Unit**

Fig. 5 is a flow chart illustrating the specifics of the operation of the converter unit 105. In step 501 the converter 211, 212 or 213 receives the decoded PA from decoder 104. In step 502, the converter looks up the decoded PA in the reference table. In step 503 the converter 211, 212 or 213 determines if the PA is listed in the table. If it is not, the sequence goes to step 504 where the user is told of the error, after which the sequence goes to step 301 where the caller may reenter the PA. In an alternate embodiment, after informing the caller of the error in step 504, the call ends. The system could also easily be extended such that if a user enters a PA that is not in the database, that the system would suggest a close match. For example, suppose both "IBM service" and "IBM sales" were preregistered PA's, but "IBM repairs" was not. If a user entered "IBM repairs" as a PA, the system might use conventional artificial intelligence (AI) to suggest "IBM service" but not "IBM sales." Such functionality might be further extended so that the system could accept a freeform statement or query such as "My IBM PC is broken, and I need to fix it." In response, the system would use conventional AI techniques to parse the statement for content, and with the retrieved content further use conventional AI to suggest the PA "IBM service."

When no error is found in step 503, the sequence proceeds to step 505, where the converter 211, 212 or 213 determines whether the PA is ambiguous. When the PA is unambiguous, in other words when it maps to only one phone number and the PA owner has placed no restrictions on callers who can contact that corresponding phone number via the PA, the sequence proceeds to step 505a. In step 505a converter 211, 212, or 213 uses the reference table to determine a telephone number. After step 505a, flow proceeds to step 507.

In the case where the PA is ambiguous, in other words maps to two or more phone numbers or the PA maps to only one phone number but is restricted, the process passes to step 506 in order to resolve the ambiguity before passing to step 507. The details of ambiguity resolving step 506 are explained below. In step 507 the converter 211, 212 or 213 outputs the telephone number that, according to the reference table, corresponds to the entered PA. In step

508 the output is sent to the appropriate portions of the CO 101, CC 107, or the like so that the contact between the caller and the party associated with the entered PA can be established.

An example of an unambiguous PA can be seen in the sample reference table (Fig. 7) where we see that the PA "mary zigelbrat ny" maps only to the phone number 818-323-8080. On the other hand, the sample reference table notes that "police emergency" is ambiguous and maps to a plurality of phone numbers. In a case such as this it is up to the system to resolve the ambiguity in order to connect the caller to the proper police station

Operation of the Converter Unit: Resolution of Ambiguity

10 ~~Fig. 6 is a flowchart detailing ambiguity resolving step 506.~~ In step 601, the converter 211, 212 or 213 consults the reference table 700 in order to determine what parameter needs to be determined in order to resolve an ambiguity. In other words, it is determined what additional information needs to be gathered. Depending on the result of step 601, the system will proceed to one of steps 602, 603, 604, or 605.

15 If, in step 601, converter 211, 212 or 213 determines that the parameter is the caller's present location, the flow proceeds to step 602 where converter 211, 212 or 213 determines the current location of the caller (latitude/longitude coordinate). If in step 601 it is determined that the parameter to be the telephone number the call is being placed from, the flow proceeds to step 603 where converter 211, 212 or 213 determines the telephone number the call is being placed from. If it is determined in step 601 that the parameter is the caller's identity, the flow proceeds to step 604 where converter 211, 212 or 213 determines the identity of the caller. If it is determined in step 601 that the parameter is the caller's response to one or more queries, the flow proceeds to step 605 where the system asks the caller one or more questions provided by the table. In one embodiment, the user will answer such questions using the keypad or keyboard. In another embodiment voice input may be employed, using one of the voice

20

25

recognition methods that are well known in the art. Steps similar to steps 602-605 may be added for embodiments in which additional parameters are used to resolve ambiguities.

sub 03
In step 606 it is determined whether converter 211, 212 or 213 was able to successfully determine the necessary parameter. If not, the process proceeds to step 607 where the caller is informed of the error (e.g., by a voice or on-screen message), and then to step 301 where the caller may reenter the PA. In an alternate embodiment, after converter 211, 212 or 213 informs the caller of the error in step 607 the call ends.

If the necessary parameter has been successfully determined, the process goes to step 608. Here converter 211, 212 or 213 consults the reference table, in light of the entered parameter, to resolve the ambiguity and determine a phone number. In step 609 it is determined whether step 608 was successful (i.e., if the entered PA in light of the determined parameter resulted in a phone number) or unsuccessful (i.e., if the entered PA in light of the determined parameter did not result in a phone number). If step 608 was not successful, the process proceeds to step 607 where the converter 211, 212 or 213 informs the caller of the error, and then to step 301 where the caller may reenter the PA. In an alternate embodiment, after informing the caller of the error in step 607 the call ends. Step 608 might be unsuccessful, for example, if the caller, because of his location, phone number, group, identity (ID), or query answers, is not entitled to be connected to any of the parties who have registered the entered PA. If step 608 was successful, the flow proceeds to step 507 where the converter 211, 212 or 213 outputs the telephone number that, according to the reference table, corresponds to the entered PA.

The Reference Table

The use of the reference table rather than keypad encoding means that any PA mnemonic can be assigned to any telephone number. For example, unlike keypad encoding “hotdogs” and “hotfogs” could both be assigned as mnemonics. This is possible because the present system sees these as completely different mnemonics since they have different

alphanumeric constructions. Further, whereas in the keypad encoding system “hotdogs” had to correspond to 468-3657, in the present system “hotdogs” may correspond to any available telephone number. Further “hotdogs” could be assigned as a PA, even if the PA “hotdogs” were assigned to a second party and the telephone number 468-3657 corresponded to a third party.

5 Phone addresses may be correlated with telephone numbers by the table in a variety of ways. In one embodiment, the system administrators may register (assign) “generic” PA's for users, and these users may choose additional “vanity” PA's for a fee. For example, when PA service comes to the neighborhood of Frank Jones of Upper West Side, Manhattan, he is assigned a first generic PA in the form of “frank jones upper west side,” and a second generic
10 PA that is numerically equivalent to the telephone number he had been previously assigned. The table maps both PA's to his home phone number. For an extra fee, he may choose to register another phone address to either replace or augment his generic ones. For example, Mr. Jones may choose to register the phone address “big sports fan.” If he chooses “replace”, one or more of his two assigned PA's will be removed and only “big sports fan” and will map to his home phone. If he chooses “augment”, all three phone addresses will map to his telephone number. Alternately, as will be described in detail later, Mr. Jones may opt to have “deluxe unlisted”
15 PA's, which are only valid under certain conditions. Further, a user may choose multiple PA's, perhaps with different features, which all map to the, same telephone number.

Fig. 7 is a sample reference table according to one embodiment. Column 710 of
20 the table is the “keypad equivalent” column. It lists keypad/numeric keypad sequences which resolve to preregistered PA's. The column 720 of the table is the “PA” column which lists the preregistered PA's. It is related to the first column such that it notes for each keypad sequence the preregistered PA's that correlate to that keypad sequence.

The column 710 is only used for keypad or numeric keypad PA input. For
25 example, if a keypad user entered “4283267269”, in step 402 the decoder 210, 212 or 213 can look up this keypad sequence in column 710 and learn from column 720 that the corresponding

preregistered PA's are "have company" and "hate company." The decoder would proceed to determine which PA was intended by the user. On the other hand, if the user entered "have company" using form of input other than keypad or numeric keypad, such as voice or keyboard, there would be no need to consult the column 710 in order to determine which PA was intended.

5 The column 730 is the "ambiguity resolving parameter" column. It is related to the column 720 such that it notes for each ambiguous PA what parameters resolve the ambiguity, and for each unambiguous PA a NULL value. The column 740 is the "parameter possibilities" column. For each entry in the "ambiguity resolving parameter" column, it notes the values of that parameter that are recognized by the system. For example, if the "ambiguity resolving parameter" column noted "actual location of user," the "parameter possibilities" column would list specific location values for that parameter. When the PA is unambiguous, column 730 lists a NULL value for the PA.

10 The column 750 is the "telephone number" column. For unambiguous PA's, it is related to the column 720 such that it lists the telephone number that relates to an unambiguous PA of the column 720. For ambiguous PA's, it is related to the column 740 such that it lists the telephone number that relates to an ambiguous PA of the column 720 in light of a parameter value noted in the column 740.

15 The PA "mary zigelbrat ny" is an example of an unambiguous listing. Thus the ambiguity resolving parameter (ARP) column 730 states "NULL" to denote that there is no ambiguity to be resolved, as does the parameter possibilities (PP) column 740. The telephone number (TN) column 750 notes that the corresponding listing for "mary zigelbrat ny" is 212 323 8080. In addition to being an example of a unique listing, the listing for "mary zigelbrat ny" is also an example of a generically assigned PA as discussed earlier.

20 The PA "303 456 8018" is, in addition to being an example of an unambiguous PA, an example of one method by which the PA system can allow people in an area with PA service to call parties that live in an area that does not offer PA service. In this method, for each

phone number in an area that is not served by PA service, a PA consisting of the numerals that make up the telephone number is listed to map to that phone number. For example, since the phone number 303-456-0818 is not served by PA service, the table lists a PA “303 456 0818” which maps to the phone number 303-456-0818.

5 A similar method can be used to allow users in a PA area to call a party using that party’s phone number instead of that party’s PA. The PA’s “2123238080” and “mary zigelbrat, ny” both map to the telephone number 212-323-8080. Hence most users would probably contact the party using the easier-to-remember “mary zigelbrat, ny”, while those who were comfortable using her telephone number to contact her could continue to do so.

10 For ambiguous PA’s, in some cases the resolution of the ambiguity will be “automatic” from the viewpoint of the caller, while in other cases it will be interactive. The PA “police emergency” is an example of an ambiguous listing where the resolution of the ambiguity is automatic. In this example, the corresponding ambiguity resolving parameter is the actual location of the caller. The PP column 740 notes several parameter values, and the TN column 750 notes the corresponding phone number for each parameter value. For example if the entered PA was “police emergency”, and the location of the caller was found to be “1 mi. radius of 40.76Lat, -73.97 long,” the corresponding phone number would be 212 888-4238. The resolution is automatic because location data can be provided to the system from a GPS device in the caller’s phone or mobile, and thus the system can learn the user’s location without interacting
15
20 with the user.

On the other hand, the PA “big football fan” is an example of an ambiguous listing where the resolution of the ambiguity is interactive, as converter 211, 212 or 213 must ask the caller questions in order to resolve the ambiguity. Consulting table 700, for this PA ARP column 730 lists “query caller...”, further noting that converter 211, 212 or 213 should ask the
25 user to “press 1 or say ‘fred’ if it’s fred williams of Bayonne, press 2 or say ‘johnny’ if it’s Johnny Parker of Freemont” If, for example, the caller said “johnny”, converter 211, 212 or

213 consults PP and PN columns 740 and 750 of the table 700 and notes that when the parameter value is "johnny" the number is 415-232-2222. Although this example shows one question being asked of the caller, in practice one or more queries could be directed at the caller.

The listing of the PA "national metro pizza delivery" is another example of an ambiguous PA where the ambiguity can be resolved without consulting the caller. Referring to table 700, we see that the ARP column 730 tells the converter 211, 212 or 213 that the ambiguity is to be solved based on the phone number of the caller. The phone number of the caller is determined by using, for example, ANI (automatic number identification). If, for example, the caller's number is found to have a 212 area code, consulting the PP and PN columns 740 and 750 shows that the proper phone number is 212-606-6666.

The sample PA "mommy" is a case of an ambiguous PA where the ambiguity is resolved using the identity of the caller. Referring to table 700, for the PA "mommy" ARP column 730 discloses that voice sample identification is to be used, and that the voice sample of the caller is to be obtained by having the caller repeat the sentence "The United States Of America." The converter 211, 212 or 213 then compares the voice sample of the caller with voice samples stored in a database so as to determine the identity of the caller. Looking at the PP and PN columns 740 and 750, if the identity of the caller is determined to be "Kevin Melkin #338", then the appropriate phone number is 201-434-0212. On the other hand, if the caller is determined to be "Marsha Stuart #221", the appropriate phone number is 618-484-2121.

In order to compile the voice sample database, users who plan on calling PA's that require voice authentication submit a voice sample to the system at a point prior to making the call. For example, such a sample could be given at a local phone company office where the identity of the person submitting the voice sample could be verified using a passport or other form of identification. In another embodiment, instead or in addition to using voiceprint authentication, the caller might be asked to enter an identification code and password. Further, handwriting recognition could be used as a means of confirming the ID of the caller instead or in

addition to the above-described methods. In embodiments that use handwriting recognition for PA entry, the system could operate such that it would determine the identity of the caller based on the personally-identifying characteristics of the way in which the caller entered the PA. In other embodiments, the user might be asked to write a specific phrase such as "The United States of America."

In step 609 of Fig. 6, if the value obtained for the parameter does not correspond to a telephone number, flow proceeds to step 607 where converter 211, 212 or 213 logs the error.

For a PA like "mommy" this means that if the caller's voice sample does not match a voice sample on file, the person will not be connected to a party. Thus in addition to this method connecting a caller who enters "mommy" with the proper party, it also offers the security feature by which, for example, no one but Kevin and Ben can connect to 201-434-0212 by entering the PA "mommy."

If the party who owns the telephone number 201-434-0212 further chooses to have no insecure PA's map to this phone number, and have the actual phone number be unlisted, a "standard secure" respectable level of security can be established in which the only people who can reach 201-434-0212 are those who enter the PA mommy with identities that were granted access by the owner of 201-434-0212, or parties from a non-PA service area who have somehow learned of the unlisted telephone number.

If, however, no insecure PA's map to this number, and people from non-PA service areas are prevented from reaching this number, then a high level of security, "deluxe unlisted/deluxe secure", will be achieved in which the only people who can reach 201-434-0212 are those who enter the PA mommy and whose identities were granted access by the owner of 201-434-0212.

In a related embodiment, a user could order an "expiring listing PA." For example, a professor can give out in class a PA that the table would map to his telephone number during the semester, but which would stop working after the semester ends. In some

embodiments, the caller may hear "this PA has expired. There is no further information available." When coupled with a deluxe unlisted PA for which none of his students has access privileges, or a standard unlisted PA that the students did not know, his students would not be able to reach him once the semester was done.

5 The features of "deluxe secure" and "standard secure" do not require a PA that maps to more than one phone number. As discussed previously, "ambiguous" PA's are not only those PA's which map to more than one phone number, but also those PA's that map to a single phone number but for which restrictions have been placed on what callers can use the PA to access the corresponding phone number. For example the PA "fanny hagelman" maps to only
10 one phone number, but Ms. Hagelman has placed voice sample restrictions on who may use that PA to reach her. The PP column 740 for this PA denotes that only "Harry Fengel #12" may contact Ms. Hagelman using this PA; all other users entering PA "fanny hagelman" would be denied access.

15 In some embodiments, the system may be set up so that a user may set up aliases to commonly-entered PA's. Such aliases would be similar to aliases presently in use in computer file systems, email systems, and the like. For example, if a user calls the PA "Metro Pizza Delivery" often, he might choose to set up "my pizza" on his telephone as an alias to that PA. The user could subsequently enter "my pizza" to the same effect as entering the PA "metro pizza delivery."

20 Although the description above contains many specificities, these should not be construed as limited the scope of the invention but as merely providing illustrations of some of the presently preferred embodiments of this invention. Thus it will be apparent to those skilled in the art that various modifications and variations cab be made in the system and processes of the present invention without departing from the spirit or scope of the invention. Accordingly, it
25 is intended that the present invention cover its modifications and variations provided they come within the scope of the appended claims and their equivalents. In this context, equivalents

means each and every implementation for carrying out the functions in the claims, even if not explicitly described herein.

09846830-050101
FOI050-06294860